


Enfriador refrigerado vertical ERC 36 B





Enfriador refrigerado vertical ERC 36 B

EXTERIOR

- Acero plastificado blanco
- Cabeza iluminativa (ERC 17/36)

INTERIOR

- Acero plastificado blanco
- Iluminación LED interior
- Parrillas de alambre de acero plastificado, regulables en altura y fácilmente desmontables

AISLAMIENTO

- Poliuretano inyectado alta presión libre de CFC's densidad 40 kg/m³, bajo GWP y cero efecto ODP

PUERTAS

- Puertas con doble acristalamiento (6-10-4)
- Burlate fácilmente sustituible
- Puertas con tirador integrado

REFRIGERACIÓN

- Sistema de condensación ventilada
- Evaporadores tratados anticorrosión 100% Poliéster
- Bandeja evaporativa en acero inoxidable
- Control temperatura final del desescarche

OPCIONAL / OPTIONAL

- Parrillas / Wire shelves ERC 17/36 (502X27)

EXTERIOR

- White plastic coated steel
- Illuminated head (ERC 17/36)

INTERIOR

- White plastic coated steel
- LED interior lighting
- Plastic coated wire shelves, adjustable height and easy removal

INSULATION

- Free CFC's high density (40kg/m³) polyurethane insulation with low GWP & zero ODP effect

DOORS

- Doors with double glass. (6-10-4)
- Easy removal gasket
- Integrated handle doors

REFRIGERATION

- Forced air refrigeration system
- Evaporator coil coated with anti-corrosion material 100% Polyester
- Stainless steel evaporative tray
- Control of the final defrost temperatura

MODELOS MODELS													
	Dimensiones Dimensions LxHxP (mm)	Potencia Power (W)	Tensión/Frecuencia Electrical (V/Hz)	Capacidad Capacity (L)	Nº puertas Doors	Nº parrillas/L. guías No shelves / Slides	Compresor Compressor (HP)	Potencia Frig. Cooling capacity (W) (T _{amb} -10°C)	Evaporación Evaporation	Régimen temperatura Temperature range (32°C)	Desescarche Defrost	Control Control	Refrigerante Coolant
ERC 36 B	620x595x1870	575	220/50	355	1	4	1/4	577	Forzada Forced	+4°C/+8°C	Automático Automatic	Digital	R 404 A